



Anhui Xiaoyi Bearing Import & Export ...

2.188 Inch | 55.575 Millimeter x 3.125 Inch |
79.38 Millimeter x 2.5 Inch | 63.5 Millimeter SKF
SYR 2.3/16 H-3 Pillow Block Bearings



Bearing No. SYR 2.3/16 H-3

SYR 2.3/16 H-3 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	5.45
EAN	7316576674860
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Concentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	22211
Seals	Garter Spring
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Double Row Heavy Duty Locating Bearing Open End With Set Screw
Long Description	2 Bolt Pillow Block; 2-3/16" Bore; 2-1/2" Base to Center Height; Concentric Collar Mount; Spherical Roller



Anhui Xiaoyi Bearing Import & Export ...

	Bearing; 6-7/16" Minimum Bolt Spacing; 7-1/16" Bolt Spacing Maximum; Relu
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SYR 2.3/16 H-3
Weight / LBS	12
Bolt Spacing Maximum	7.063 Inch 179.4Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
B	2.5 Inch 63.5 Millimeter
D	3.125 Inch 79.38 Millimeter
d	2.188 Inch 55.575 Millimeter
Bolt Spacing Minimum	6.438 Inch 163.525Millimeter
Nominal Bolt Center to Center	6.8 Inch 171.5 Millimeter
bore diameter:	2.1875 in
bolt center-to-center length:	6-3/4 in
overall length:	8.8750 in
base width:	2-5/16 in
overall height:	5.0000 in
expansion type:	Non-Expansion Bearing (Fixed)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard
bore type:	Round



Anhui Xiaoyi Bearing Import & Export ...

radial dynamic load capacity:	28100 lbf
housing construction:	Solid Pillow Block
radial static load capacity:	28500 lbf
base to bore centerline:	2.5000 in
maximum rpm:	2000 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYR
locking device:	Concentric Collar
replacement bearing:	22211