



E-4BF-TRB-45MM Bearing 2D drawings and 3D CAD models

TIMKEN E-4BF-TRB-45MM Flange Block Bearings

Bearing No. E-4BF-TRB-45MM

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	5.883
EAN	0053893543994
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Metric
Long Description	4 Bolt Square Flange Block; 45MM Bore; 157MM Bolt Circle; 111.13MM Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Tapered Roller Bearing; 88.9MM Length Thru Bore; Relubricatable; Dou



Anhui Xiaoyi Bearing Import & Export ...

Other Features	Double Row Wide Inner Race With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	E-4BF-TRB-45MM
Weight / LBS	12
Bolt Spacing	4.375 Inch 111.13 Millimeter
Nominal Bolt Circle Diameter Round	6.2 Inch 157 Millimeter
D	3.5 Inch 88.9 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
d	1.772 Inch 45 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Shaft Size	1.772 in
Shaft Size Type	Metric
Weight	12 lb
UPC Code	053893543994
Dimension B	3-1/2 in
Dimension L	5-5/8 in
Dimension A	3-3/32 in
Dimension J	4-3/8 in
Dimension A ₂	1/8 in
Bolt Diameter	1/2 in
Dimension A ₁	1-3/16 in
Dimension D ¹	4-7/16 in
Dimension d ₁	3-7/16 in
e	0.33
X (if F _a /F _r e)	0.87



Anhui Xiaoyi Bearing Import & Export ...

Y (if $F_a/F_r \leq e$)	2.64
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	3.18
K Factor	1.83
C_{90} Dynamic Load Rating ²	10300 lb
C_0 Static Load Rating	43000 lb
F_{a-max} Maximum Permissible Thrust Load ³	2590 lb
F_{r-max} Maximum Allowable Slip Fit Radial Load ⁴	8400 lb
Max. Speed ⁵	3050 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur